



## China abec 7 Bearings Supplier

Large stock M348449/M348410 taper roller bearing timken P6 precision timken track roller bearings for sale

Bearing No. M348449/M348410



M348449/M348410 Bearing 2D drawings and 3D CAD models

|                               |                        |
|-------------------------------|------------------------|
| Size                          | 247.65x346.075x63.5 mm |
| Bore Diameter                 | 247,65 mm              |
| Outer Diameter                | 346,075 mm             |
| Width                         | 63,5 mm                |
| d                             | 247,65 mm              |
| D                             | 346,075 mm             |
| T                             | 63,5 mm                |
| B                             | 63,5 mm                |
| C                             | 50,8 mm                |
| R                             | 6,3 mm                 |
| r                             | 6,3 mm                 |
| a -                           | 1,3 mm                 |
| Da                            | 332 mm                 |
| db                            | 273 mm                 |
| da                            | 263 mm                 |
| Db                            | 321 mm                 |
| Aa                            | 4 mm                   |
| Ab                            | 3,6 mm                 |
| Weight                        | 17,59 Kg               |
| Basic static load rating (C0) | 1620 kN                |
| Factor (G1)                   | 1450,8                 |
| Factor (G2)                   | 212,9                  |
| Factor (Cg)                   | 0,0436                 |
| Factor (K)                    | 1,7                    |
| Basic dynamic load rating     | 204                    |



## China abec 7 Bearings Supplier

|                                     |        |
|-------------------------------------|--------|
| (C90)                               |        |
| Basic dynamic load rating<br>(Ca90) | 120    |
| Basic dynamic load rating<br>(C1)   | 787 kN |
| Calculation factor (e)              | 0,34   |